

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problems Mailbox.**

Requested Patent: GB2058367A
Title: REGULATOR TESTER ;
Abstracted Patent: GB2058367 ;
Publication Date: 1981-04-08 ;
Inventor(s): ;
Applicant(s): SHELLER GLOBE CORP ;
Application Number: GB19800026440 19800813 ;
Priority Number(s): US19790070806 19790829 ;
IPC Classification: G01R31/00 ;
Equivalents: CA1155180

ABSTRACT:

Testing apparatus and method for testing a regulator for switching current to an external load device in response to applied voltage, e.g., field current of an alternator. A power delay circuit is connected across the terminals of the regulator and supplies load current to a third terminal when the regulator is turned on by charging a capacitor in the delay circuit. When the charge on the capacitor reaches a high limit, the regulator switches off and load circuitry is switched on to ramp the capacitor voltage downwardly until the regulator again switches on. The load circuitry at that time switches off. An auxiliary power supply is effective when the regulator is switched on to supply additional load current.


(12) UK Patent Application (19) GB (11) 2 058 367 A

(21) Application No 8026440
 (22) Date of filing 13 Aug 1980
 (30) Priority data
 (31) 70806
 (32) 29 Aug 1979
 (33) United States of America (US)
 (43) Application published 8 Apr 1981
 (51) INT CL³
 G01R 31/00
 (52) Domestic classification
 G1U C12
 (56) Documents cited
 GB 1508774
 (58) Field of search
 G1U
 (71) Applicant
 Sheller Globe Corporation
 P.O. Box 962, Toledo,
 Ohio 43697, U.S.A.
 (72) Inventor
 George K. Korbell
 (74) Agents
 A. A. Thornton & Co.
 303—306 High Holborn,
 London WC1V 7LE

(54) Regulator Tester

(57) Testing apparatus and method for testing a regulator for switching current to an external load device in response to applied voltage, e.g., field current of an alternator. A power delay circuit is connected across the terminals of the regulator and supplies load current to a third terminal when the regulator is turned on by charging

a capacitor in the delay circuit. When the charge on the capacitor reaches a high limit, the regulator switches off and load circuitry is switched on to ramp the capacitor voltage downwardly until the regulator again switches on. The load circuitry at that time switches off. An auxiliary power supply is effective when the regulator is switched on to supply additional load current.



GB 2 058 367 A




FIG. 1




FIG. 2

SPECIFICATION Regulator Tester

The present invention relates to a testing apparatus and a method for testing regulators for electrodynamic machines for providing electric power. The invention has particular application to static regulators for controlling the field current of alternators such as alternators for vehicles which are driven by variable speed engines to supply battery charging current and DC load current for accessories etc. through a load rectifier and to such a testing apparatus and method which does not require a running alternator or a load battery set up to effect a testing of the regulator.

The regulators to be tested commonly involve a voltage sensing circuit for sensing a voltage applied to the regulator and for switching a field switching device to a conductive or nonconductive condition to control field current to a machine to control the output voltage thereof. When the field switching device is controlling an alternator or the like and is in a conductive condition, field current flows to the field and when in a nonconductive condition, the field current is off. The voltage sensing circuitry normally includes semiconductor components, e.g., a Zener diode and a control transistor for switching on and off the field switching device which is commonly a transistor or transistors, e.g., a Darlington circuit arrangement. Also, alternator regulators are commonly provided with a diode circuit which is connected directly to the AC output of the armature windings of the alternator. The purpose of the diode circuit is to provide a voltage when the alternator is rotating, particularly on starting, to operate a switching circuit, commonly a transistor, in the regulator for causing the application of the voltage across the terminals of the regulator to the voltage sensing circuitry and to the field switching device. The regulator then operates to switch on the field switching device until the voltage rises to a maximum voltage regulation level. At this time, the voltage sensing circuit switches the field switching device off until the voltage drops to a lower voltage regulation level at which the voltage sensing circuitry again switches on the field current. The voltage sensing circuit commonly includes an adjustable voltage dividing circuit, e.g., a potentiometer, for adjusting the voltage at which the switching occurs as well as other components such as a capacitor for effecting fast switching and proper operation of the circuitry and a zener diode which switches on and off at the high and low voltage regulation levels.

Various types of testers have been utilized to test voltage regulators. One type of known tester is a static tester which utilizes a variable power supply and voltmeter, with the variable power supply being adjustable to various voltages to determine the switching voltages of the regulator. However, the measurement of the voltage setting in this type of tester is generally unpredictable

65 with errors of up to .5 volts.

Dynamic testers have also been utilized. These testers have been open loop testers which periodically apply a voltage such as an A.C.

70 switch at the applied frequency. The measurement of voltage settings of such a tester will not commonly provide a performance test for various vital parts of a regulator, for example, capacitors.

75 The present invention involves a closed loop regulator tester in which the regulator is loaded with electronic circuitry which simulates the alternator and battery system so that the regulator responds in a manner which closely
80 parallels its use in the actual system and eliminates the need for a running alternator or a battery hook-up.

The present invention provides a testing apparatus for testing a regulator having first and
85 second terminals to which a voltage is to be applied to effect the switching off and on by the regulator of an external load circuit as the voltage varies between high and low regulation levels with the regulator having a voltage sensing circuit
90 connected across the terminals and a third terminal for connection to the external load device also connected to one of the first and second terminals with a switching device being connected between the third terminal and one of
95 the first and second terminals to switch a load current for the external device, said apparatus comprising a power supply having an output, power delay means connected to the output of the power supply, first means for connecting the
100 output of the power delay means across the first and second terminals of the regulator, load circuitry connected to the output of said power delay means to lower the output voltage from the power delay means to the first and second
105 terminals of the regulator comprising switching means having a control element, second means connectable to the field terminal to provide a load circuit for the switching device of the regulator and for connecting said control element to the
110 field terminal to render said switching means responsive to the voltage on the field terminal when the switching device of the regulator under test is nonconductive to switch on the load circuitry and to switch off the load circuitry when
115 the switching device of the regulator is conductive, and means for indicating the state of the switching device of the regulator.

The present invention also provides a method of testing a regulator for regulating the field
120 current to an electrodynamic machine for supplying electric power to a load where the regulator has a semiconductor switching device for switching the field current of the machine off when the machine output voltage rises to a high
125 level and for switching the field current on as the voltage falls to a lower voltage level with the switching device being connected to a field terminal of the regulator so that the voltage of the field terminal rises and falls between high and low

levels with the switching of the switching device, connecting the regulator terminals normally connected across the output of the machine across a capacitor, charging the capacitor from a power supply through a charging circuit with the voltage of the power supply being higher than the high level of voltage regulation for the regulator to cause the field switching device of the regulator to switch off when the voltage across the capacitor is at the high regulating voltage, establishing a circuit to the field terminal to provide a load circuit through the switching device when turned on, sensing the voltage at the field terminal and switching on a switching device to load the capacitor and to effect a discharge thereof to lower the voltage of the capacitor and to effect a switching on of the field switching device at the low level of regulation, and determining the voltages across the capacitor at which the regulator switches on and off.

In accordance with the preferred embodiment of the invention, a voltage is applied to the regulator from a power supply through a delay circuit. The magnitude of the voltage is such that it will cover the full range of voltages at which regulators to be tested are to switch off. This power supply to the delay circuitry need not be varied during the testing of a regulator. When the applied voltage from the delay circuit reaches a level at which the regulator switches off, the switching of the regulator connected into the tester activates load circuitry which is connected across the delay device to lower the voltage across the regulator according to the time constant of the delay device. The voltage across the regulator then decreases along a ramp until the sensing circuit of the regulator causes the regulator to turn on which causes the load circuitry to turn off. This corresponds to the regulator switching to a condition to turn on the field current in an alternator. At this point, the voltage starts to rise along a ramp until the regulator again switches off to start a new cycle. An indicating light may be used to indicate the status of the regulator and the load circuitry, i.e., on or off, and the voltage at the output of the delay circuit may be measured to indicate the voltage at which the switching occurs.

The tester preferably has circuitry connectable to a field terminal of the field regulator to provide load current to the switching device of the regulator when the latter is turned on and the load circuitry preferably has a control switch which is responsive to the voltage at the field terminal to switch the load circuitry on and off.

The voltage tester also preferably includes a connection for supplying a voltage to a rectifying circuit of a regulator to enable the switching on of circuitry for connecting terminals of the regulator across which the voltage to be regulated is applied to the regulating circuitry of the regulator. This provides a test of the rectifying circuit of such regulator and also enables the turning on of the voltage regulator.

The present invention also contemplates the provision of an auxiliary power supply which is connectable to a field terminal to supply additional load current to the field switching device when the regulator is in a field current conductive condition.

Preferably, the delay circuitry includes adjustable circuitry for varying the time rate of the power delay to control the rate of on-off cycles of the regulator.

It will be understood that while the invention relates to static regulators for alternators and similar machines, it is applicable to similar regulators for switching current to an external device on and off in response to changes in an applied voltage.

The preferred embodiment of the present invention will be described with its reference to the accompanying drawings forming a part of the present specification for all subject matter disclosed therein and in which:

Figure 1 is a block diagram of the tester with a regulator connected therein;

Figure 2 is a circuit diagram of the preferred embodiment of the present regulator; and

Figure 3 is a circuit diagram for a typical regulator to be tested.

Referring to the drawings, the testing apparatus of the present invention includes a dc power supply 10 for supplying power through a delay circuit 12 to a regulator 14 to be tested. The regulator 14 when switched to a condition which would switch off the field current of an alternator in an actual system activates load circuitry 16 to draw load current from the delay device 12 to lower the voltage applied from the DC power supply 10 through the delay circuitry to the regulator 14 at a rate dependent upon the time constant of the delay circuitry and the load current.

Referring to Figure 2, the type of regulators to be tested commonly have three terminals: DC power supply terminals 16, 18 and field terminal 20, commonly designated on automotive type regulators as "—F". The voltage of the —F terminal will be at high and low voltage levels when the regulator is off and on respectively (the —F designation is not a polarity designation).

As illustrated in Figure 2, the particular regulator to be tested comprises regulating circuitry including a voltage sensing circuit 21 connected across the DC terminals 16, 18 and a field switching device 22, which conventionally is a transistor, connected between the field terminal 20 and the negative DC power terminal 18. On application of dc power to the regulating circuitry, the field switching transistor will be turned on until the voltage sensing circuit senses that the voltage across the terminals 16, 18 is at a high regulation level at which the field circuit is to be switched off. At this point, the transistor 22 will be switched to a nonconductive condition and will remain in a nonconductive condition until the voltage drops to a low regulation level. At the low regulation level the regulating circuitry will

operate in a conventional manner to switch the transistor 22 to a conductive position. When operating to control an alternator or the like with the illustrated type regulator, the field coil of the alternator would be connected to the positive terminal 16 and the -F field terminal 20 to complete the load circuit for the field switching transistor 22. The tester is provided with a circuit connection as explained hereinafter to provide load current for the field switching transistor 22.

As illustrated in Figure 2, the power supply 10 of the testing apparatus includes a transformer 26 having its primary coil connected to a source of AC current, preferably 110 volts, and its secondary coil connected to a full wave rectifier bridge 28. The rectifier bridge 28 has output terminals 29, 30 with the terminals being connected to the input of the delay circuitry 12. The delay circuitry 12 includes a capacitor 32 with the positive bridge terminal 30 being connected to the capacitor 32 through a charging resistance 34 and the negative bridge terminal 29 being connected to the opposite side of the capacitor 32, ground in the illustrated circuit, by a lead 35. The tester has leads 38 and 40 to be connected to the regulator to be tested which are respectively connected to the positive and ground sides of the capacitor 32. In addition, the tester includes a lead 42 connected to the positive side of the capacitor 32 by a switch 44. The lead 42 provides a connection to a diode trio terminal of the regulator for effecting a turn on of the regulator in response to an AC voltage on the windings of the alternator.

The tester also has load circuitry comprising a resistor 54 and a switching device, preferably a transistor 50, connected across the capacitor 32, i.e., the output of the delay circuitry. The collector of the resistor 50, an NPN transistor in the illustrated embodiment, is connected to the positive side of capacitor 32 through resistor 54 and the emitter is connected to the ground.

The tester further includes a lead 48 to be connected to the -F field terminal 20 of the regulator to provide load current for the transistor 22. The lead 48 is also connected to the base of the transistor 50 through a resistance 52 and to the positive side of the capacitor 32 through a resistor 53. Preferably, an indicating circuit 56, which may be a simple transistor switch controlled by the voltage at the -F terminal, for effecting energization of an indicating light 58 is connected to the lead 48 and operates to indicate the on or off condition of the regulator under testing by turning the light on and off. Such circuit arrangements are well within the ability of those skilled in the art.

In operation, the regulator is connected into the tester by connecting the leads 38, 40 and 48 of the tester to the regulator terminals 16, 18 and 20 respectively. The diode lead 42 is also connected and operates internal regulator circuitry for switching the voltage applied to the terminals 16, 18 to the regulator circuitry for sensing voltage and applying a control signal to

the field switching device 22 for switching the latter. This will effect an initial turn on the field switching transistor as the voltage on capacitor 32 builds up to the high level of regulation where the regulator is switched off by the voltage regulating circuit. When the regulator transistor 22 is conducting, load current is drawn through the resistor 53 and lead 48 and the voltage at the -F terminal 20 is at a low level (about 1 volt). At this time the transistor 50 of the load circuitry is turned off. It will be appreciated that the resistor 53 relative to the charging resistor 34 is such that the voltage on capacitor 32 will ramp upwardly with the transistor 22 conducting. When transistor 22 switches off, the voltage of the -F terminal rises to a voltage which switches on the load circuitry of transistor 50, the voltage at the -F terminal being the voltage across the positive and negative poles of the regulator reduced by the dividing ratio of resistor 53 and resistor 52.

In the preferred embodiment, an auxiliary voltage supply comprising a transformer 64 and a full wave rectifying bridge 66 having positive and negative terminals 68, 70 is connected into the circuit to supply additional load current for the switching device 22 when the regulator is in a turned on state. The positive terminal 68 is connected to the lead 48 and, in turn, to the -F field terminal 20 of the regulator under test, by a connection including series connected resistor 71 and diode 72.

In operation, when the regulator is switched on, the voltage at the -F terminal drops to a low level and load current will flow from the auxiliary power supply as well as from the capacitor 32 through the resistor 53. When the voltage across the regulator under test rises, and the regulator turns off, the field switching transistor 22 becomes nonconductive and the voltage of the terminal 20 will rise and back bias diode 72 so that the auxiliary power supply is effectively disconnected from the circuit.

When the regulator turns off, the voltage of the -F field terminal rises to a voltage which is higher than the unloaded voltage from the auxiliary power supply 66 in order to effect a back biasing of the diode 72 but is below the voltage across the regulator because of the voltage divider formed by resistors 53, 52. The advantage of this configuration lies in the relatively low voltage power requirements of the power supply 66 necessary to provide load current for the field switching transistor when it is in an on condition. Commonly, the field switching transistor 22 of the regulator has a 4 ampere load with a 12 volt alternator rotor (48 watts). The power supply requirements for such a regulator for a 3 volt auxiliary power supply would be 3 volts x 4 amps or 12 watts for a full duty cycle or 6 watts for a half duty cycle to provide a 4 amp current load for the transistor (1 volt across the transistor when conducting).

Figure 3 is a schematic of a type of conventional regulator for testing the apparatus of Figure 2. Referring to Figure 3, the regulator is

shown connected to an alternator and includes field switching transistor 22 for switching field current on and off to a field coil 80 of an alternator. The transistor 22 in the illustrated regulator is connected between the -F field terminal 20 of the regulator and the negative terminal 18. The transistor 22 is turned on by conventional switching circuitry connected across the terminal 16, 18 of the regulator. This circuit includes a PNP transistor 74 having its emitter connected to the positive regulator terminal and its collector connected to a resistor 76, the resistor 76 being connected to the base of transistor 22 to conduct base current thereto and to the collector of a transistor 78 having its emitter connected to the negative terminal 18. When the transistor 74 is in an on condition, base current is supplied to the transistor 22 to turn it on, unless the transistor 78 is conductive to effectively connect the resistor 86 directly to the negative terminal so that the transistor 22 is maintained in, or switched to, an off condition.

The transistor 74 is turned on in response to the output voltage of a diode trio 90 connected to the AC windings 91 of the alternator. The output of the diode trio 90 is connected through a resistor 94 to the base of a transistor 96 having its collector connected to the positive terminal 16 through resistors 100, 102, and its emitter connected to the terminal 18. A resistor 106 is connected from the output of the diode trio 90 to the negative terminal 18 to parallel the base-emitter circuit of transistor 96 including the base resistor 94. When there is an output voltage from the diode trio, the transistor 96 is turned on to establish current through the resistors 100, 102 which in turn turns on the transistor 74 by reason of its base connection to a junction between the resistors 101, 102. This effects a turn on of the field switching transistor 22 as long as the transistor 78 is nonconductive.

A voltage sensing circuit comprising resistors 110, 112 is connected from the collector of transistor 74 to the negative terminal 18. A zener diode 116 which will break down and become conductive to turn on the transistor 78 when the voltage applied across the terminals 18, 16 reaches a maximum value of regulation. The voltage at which the zener diode breaks down can be adjusted by adjusting the ratio of the resistors 110 and 112. For this purpose, resistor 112 is shown as adjustable. The resistor 112 is conventionally paralleled by a capacitor 118 and a resistor 120 is conventionally connected between the base of the transistor 78 and the negative terminal 18.

From the foregoing description of the regulator, it can be seen that when the tester (Fig. 2) applies a DC voltage across the regulator terminals 16 and 18 and to the diode trio, the regulator will supply base current to the transistor 22 through the operation of transistors 96 and 74. A load circuit is provided for the field switching transistor 22 when in the tester of Fig. 2 from the capacitor 32 through the lead 48 of the tester to the -F

terminal 20. The regulator will remain in an on condition, i.e., transistor 22 conducting, until the voltage across the terminals 18 and 20 due to the ramping up of the voltage on capacitor 32

reaches a level where the Zener diode 116 breaks down to switch on the transistor 78 and render the transistor 22 nonconductive. If the capacitor 32 is fully charged when the connections are made to regulator 14, the regulator will be switched off by the action of its voltage sensing circuit.

As long as the transistor 22 is conductive, the voltage at field terminal 20 will be a low voltage and the load circuitry transistor 50 will remain in an off condition. When the transistor 22 is switched off by the voltage on capacitor 32, the voltage at the -F field terminal will rise to a value determined by the ratio of the resistors 53, 52 and as the voltage rises the load transistor 50 will be switched on to activate the load circuitry. The load circuitry will then operate as previously described and provides a simulation of a load on the alternator when the regulator is off and the voltage on the capacitor 32 will ramp downwardly until the zener diode 116 becomes non-conductive at the low regulation level to turn off transistor 78 to turn on transistor 22. It is understood that the downward ramp of the capacitor voltage is determined by the relationship of load resistor 54 and charging resistor 34.

The tester effects a test of all the vital circuit components of the regulator and is operative in the preferred embodiment with the auxiliary power supply to apply load current to the transistor 22 with a relatively low wattage power supply.

It will be appreciated that the switch on characteristics of the regulator at low RPMs of the alternator where the output is due to remnant magnetism of the core can readily be determined by applying a low voltage, for example, one volt to the diode trio lead. This will determine the operation of the diodes particularly, if the regulating cycle is then operated and the average regulated voltage does not differ significantly when the full output of the delay circuit 12 is applied to the diode trio lead.

The time constant of the delay circuit may be varied by varying the resistance of resistor 34 and for this purpose resistor 34 may be adjustable. On starting and for purposes of checking the diode trio, a switch 44 may be provided for disconnecting the capacitor 32 from the diode trio lead 42. By applying low voltage (not shown), it would then be simple to determine the turn on voltage of the regulator circuitry controlled by the diode lead 42. It will also be understood that the switching circuit 56 may include an inverter and integrator so that the light is on when the voltage at terminal 20 is low and off when high.

In certain regulators, the voltage of the -F terminal may be high when the regulator is on and low when off. For such a regulator, the resistor 53 would be switched to connect it to the

negative side of capacitor 32 and an inverter would be switched into the base circuit of transistor 50 or a switch may be operated to disconnect lead 48 including resistor 52 from transistor 50 and to connect them to the base of a PNP transistor switch which connects resistor 54 to ground when the —F terminal is low.

Claims

1. A testing apparatus for testing a regulator having first and second terminals to which a voltage is to be applied to effect the switching off and on by the regulator of an external load circuit as the voltage varies between high and low regulation levels with the regulator having a voltage sensing circuit connected across the terminals and a third terminal for connection to the external load device also connected to one of the first and second terminals with a switching device being connected between the third terminal and one of the first and second terminals to switch a load current for the external device, said apparatus comprising a power supply having an output, power delay means connected to the output of the power supply, first means for connecting the output of the power delay means across the first and second terminals of the regulator, load circuitry connected to the output of said power delay means to lower the output voltage from the power delay means to the first and second terminals of the regulator comprising switching means having a control element, second means connectable to the field terminal to provide a load circuit for the switching device of the regulator and for connecting said control element to the field terminal to render said switching means responsive to the voltage on the field terminal when the switching device of the regulator under test is nonconductive to switch on the load circuitry and to switch off the load circuitry when the switching device of the regulator is conductive, and means for indicating the state of the switching device of the regulator.

2. A testing apparatus as defined in claim 1 wherein the apparatus includes an auxiliary power supply comprising an output connection for connection to the third terminal to supply current through the switching device of the regulator when the latter is conductive, and means for rendering said auxiliary power supply ineffective to supply current when said load circuitry is switched off.

3. A testing apparatus as defined in claim 1 wherein said power delay means comprises a capacitor connected across the power supply through a charging resistance, the time constant for charging said capacitor through said resistance being such that said capacitor discharges upon activation of said load circuitry to lower the voltage across the regulator being tested and said first means is effective to connect said capacitor across said first and second terminals.

4. A testing apparatus as defined in claim 2 wherein said power delay means comprises a

capacitor connected across the power supply through a charging resistance; the time constant for charging said capacitor through said resistance being such that said capacitor discharges upon activation of said load circuitry to lower the voltage across the regulator being tested and said first means is effective to connect said capacitor across said first and second terminals.

5. A testing apparatus as defined in claim 3 wherein said switching means of the load circuitry is a transistor and said second means comprises a lead connectable to said field terminal and a first resistance connecting said lead to said control element and a second resistance connecting said lead to the output of said delay circuit.

6. A testing apparatus as defined in claim 4 wherein said switching means of the load circuitry is a transistor and said second means comprises a lead connectable to said field terminal and a first resistance connecting said lead to said control element and a second resistance connecting said lead to the output of said delay circuit.

7. A testing apparatus as defined in claims 1, 2, 3, 4, 5 or 6 wherein said apparatus includes means for determining the voltage across the output of said delay means.

8. A testing apparatus as defined in claim 7 wherein the apparatus includes means for indicating the state of the load circuitry to the operator.

9. A testing apparatus as defined in claims 1, 2, 3, 4, 5 or 6 wherein the regulator includes an additional terminal for receiving a voltage and the testing apparatus further comprises means for applying a variable voltage from the power supply to an additional terminal of the regulator to effect the connection of regulating circuitry in the regulator across the first and second terminals of the regulator.

10. A method of testing a regulator for regulating the field current to an electrodynamic machine for supplying electric power to a load where the regulator has a semiconductor switching device for switching the field current of the machine off when the machine output voltage rises to a high level and for switching the field current on as the voltage falls to a lower voltage level with the switching device being connected to a field terminal of the regulator so that the voltage of the field terminal rises and falls between high and low levels with the switching of the switching device, connecting the regulator terminals normally connected across the output of the machine across a capacitor, charging the capacitor from a power supply through a charging circuit with the voltage of the power supply being higher than the high level of voltage regulation for the regulator to cause the field switching device of the regulator to switch off when the voltage across the capacitor is at the high regulating voltage, establishing a circuit to the field terminal to provide a load circuit through the switching device when turned on, sensing the voltage at the field terminal and switching on a switching device

to load the capacitor and to effect a discharge thereof to lower the voltage of the capacitor and to effect a switching on of the field switching device at the low level of regulation, and

- 5 determining the voltages across the capacitor at which the regulator switches on and off.

11. A method as defined in claim 10 including the step of supplying additional load current to the switching device from a lower voltage power supply in response to the voltage at the field terminal when the switching device is on and switching off the auxiliary power supply when the switching device is off.

12. A method of testing a voltage regulator having positive and negative terminals to which a voltage varying in accordance with a voltage to be controlled is to be applied and a field terminal to which the field of an alternator or similar machine is to be connected to complete a load circuit
- 20 which is switched off and on as the voltage across the positive and negative terminals respectively rises to a maximum voltage regulation level and falls to a lower level by a semiconductor switch

- 25 connected between the field terminal and one of the positive and negative terminals comprising the steps of charging a capacitor connected across the positive and negative terminals to a voltage for switching the semiconductor switch to a conductive condition, supplying a voltage to the field terminal to provide load current for the switching device when on and a voltage change from one level to another at the field terminal when the semiconductor switch is turned on, loading the capacitor with load circuitry when the semiconductor switch turns off to effect the discharge the capacitor to a lower level at which the regulator switches on, switching off the load circuitry when the regulator switches on, and determining the switching voltages of the regulator.

- 40 13. A testing apparatus substantially as hereinbefore described with reference to the accompanying drawings.

- 45 14. A method of testing a regulator substantially as hereinbefore described with reference to the accompanying drawings.